

SEAL TECH PRO X SAFETY DATA SHEET

=====**Section 1 – Identification**=====

Product Name: SEAL TECH PRO X

Manufacturer: (PROPRIETARY)

Chemical Name: Acrylic Elastomeric

Information Contacts:

Chemical Family: Acrylic Coatings

Emergency Phone Numbers: (800) 535 - 5053

Product Use: Roof Coating

HMIS Rating: H F R P

Product #: SEAL TECH PRO X

1 0 0 H

=====**Section 2 - Hazards Identification**=====

HEALTH HAZARDS OR RISKS FROM EXPOSURE:

ACUTE:

- **INHALATION:** Breathing excessive vapors or mist may cause nose, throat or lung irritation.
- **INGESTION:** Not an expected route of entry. Ingestion can cause distress to the digestive tract.
- **SKIN CONTACT:** Prolonged or repeated skin contact can cause irritation.
- **EYE CONTACT:** Eye contact can cause irritation.

CHRONIC: None known

TARGET ORGANS: ACUTE: Eye, Respiratory System, Skin.

CHRONIC: None Known

=====**Section 3 - Composition/Information on Ingredients**=====

CHEMICAL IDENTITY	CAS#	EC Number	Weight %	Hazard Classification
Water	7732-18-5	231-791	35 - 40%	Non Hazard
Acrylic Copolymer	Mixture	-	45- 55%	Non Hazard
Limestone	1317-65-3	-	25 - 35%	Non Hazard
Titanium Dioxide	13463-67-7	236-675-5	3 - 7%	Non Hazard

=====**Section 4 - First Aid Measures**=====

First Aid for Eye:

Flush with plenty of water for 15 minutes, including under eyelids. Seek medical attention if discomfort persists.

First Aid for Skin:

Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water.

First Aid for Inhalation:

Remove to fresh air. If having difficulty, give oxygen. If breathing has stopped, give artificial respiration. Get medical help if discomfort persists.

First Aid for Ingestion:

Seek prompt medical attention IMMEDIATELY.

=====**Section 5 - Fire Fighting Measures**=====

EXTINGUISHING MEDIA: Suitable extinguishing media: water spray, foam, dry powder

SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE: No particular hazards known

ADVICE FOR FIREFIGHTERS:

Protective equipment for fire-fighting: firefighters should be equipped with self-containing breathing apparatus and turn out gear

FURTHER INFORMATION:

SEAL TECH PRO X SAFETY DATA SHEET

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Product itself is non-combustible; fire extinguishing methods of surrounding areas must be considered.

===== Section 6 - Accidental Release Measures =====

FURTHER ACCIDENTAL RELEASE MEASURES: High risk of slipping due to leakage/spillage of product.

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES: Use personal protective clothing. Avoid contact with skin and eyes.

ENVIRONMENTAL PRECAUTIONS: Do not release untreated into natural waters.

METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP: For small amounts: Pick up with suitable absorbent material (e.g. sand, sawdust, general purpose binder, kieselguhr). Dispose of absorbed material in accordance with regulations.

For large amounts: Pump off product.

Spills shall be contained, solidified, and placed in suitable containers for disposal.

===== Section 7 - Handling and Storage =====

Handling & Storage

Store in well-ventilated area. . Keep containers closed when not in use store away from ignition sources. Store in a clean, dry area.

Other Precautions

All precautions must be observed. Empty container may retain product residue (Solid or liquid). Store protected against freezing.

===== Section 8 - Exposure Controls / Personal Protection=====

EXPOSURE LIMITS/GUIDELINES:

MATERIAL	CAS NO.	ACGIH		OSHA
CHEMICAL INGREDIENTS	CAS #	TWA	STEL	TWA
Water	7732-18-5	Not Listed	Not Listed	Non Hazard
Acrylic Copolymer	Mixture	Not Listed	Not Listed	5 mg/m ³
Limestone	1317-65-3	Not Listed	Not Listed	5 mg/m ³
Titanium Dioxide	13463-67-7	10 mg/m ³	-	10 mg/m ³

■ Personal Protection

- Respiratory Protection – Wear an appropriate, properly fitted respirator (NIOSH/MSHA approve during application and handling unless air monitoring demonstrates vapor/ mist levels below applicable limits. Follow respirator manufacturer's recommendations for selection and use.
- Ventilation – Sufficient ventilation must be provided to maintain airborne concentrations below TLV, PEL and LEL Limits as listed in section 8.
- Protective Gloves – Chemical resistant protective gloves should be worn when handling this product. Check with glove manufacturer to determine proper glove type.
- Eye Protection – Splash-proof chemical goggles should be worn.
- Other Protective Equipment – Impervious clothing and boots should be worn. Eye bath and safety shower should be provided.

SEAL TECH PRO X SAFETY DATA SHEET

- Hygienic Practices- Good personal hygiene practices are required at all times when handling chemicals. These practices include, but are not limited to, washing when safety equipment is removed, at the end of each shift or when going on breaks and especially if contamination occurs.

===== Section 9 - Physical and Chemical Properties =====

BOILING RANGE: 163.4 - 491°F

VAPOR DENSITY: Lighter than air.

COATING V.O.C.: 6.34 g/l

SOLIDS BY WEIGHT: 64.02%

SOLUBILITY IN WATER: Complete.

APPEARANCE AND ODOR: Typical for water based paints.

SPECIFIC GRAVITY (H₂O=1): 1.30-1.36

EVAPORATION RATE: Slower than the air.

MATERIAL V.O.C.: 3.37 g/l

SOILIDS BY VOLUME: 53.14%

pH RANGE: 8-9

===== Section 10 - Stability and Reactivity =====

REACTIVITY: No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals: Corrosive effects to metal are not anticipated.

Oxidizing properties: not fire-propagating.

CHEMICAL STABILITY: The product is stable if stored and handled as prescribed/indicated.

POSSIBILITY OF HAZARDOUS REACTIONS: No hazardous reactions when stored and handled according to instructions. After long storage, slight quantities of carbon monoxide may be formed. The product is chemically stable.

CONDITIONS TO AVOID: Avoid extreme heat.

INCOMPATIBLE MATERIALS: Metal salts.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, carbon monoxide, hydrocarbons.

===== Section 11 - Toxicological Information =====

TOXICITY DATA:

No LD50 Data Available

SUSPECTED CANCER AGENT:

Ingredients are found on the following lists: FEDERAL OSHA Z LIST, NTP, CAL/OSHA, IARC and therefore its considered to be, or suspected to be a cancer-causing agent by these agencies. Crystalline Silica

IRRITANCY OF PRODUCT:

Contact with this product can be irritating to exposed skin, eyes and respiratory system.

SENSITIZATION OF PRODUCT:

This product is not considered a sensitizer.

REPRODUCTIVE TOXICITY INFORMATION:

No information concerning the effects of this product and its components on the human reproductive system.

===== Section 12 - Ecological Information =====

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

ENVIRONMENTAL STABILITY:

No Data available at this time.

EFFECT OF MATERIAL ON PLANTS or ANIMALS:

No Data available at this time.

EFFECT OF CHEMICAL ON AQUATIC LIFE:

No Data available at this time.

===== Section 13 - Disposal Considerations =====

SEAL TECH PRO X SAFETY DATA SHEET

Dispose of in accordance with all local, state and federal regulations.

===== Section 14 - Transport Information =====

US DOT; IATA; IMO; ADR:

THIS PRODUCT IS NOT HAZARDOUS AS DEFINED BY 49 CFR 172.101 BY THE U.S. DEPARTMENT OF TRANSPORTATION.

PROPER SHIPPING NAME: Non-Regulated Material

HAZARD CLASS NUMBER and DESCRIPTION: Not Applicable

UN IDENTIFICATION NUMBER: Not Applicable

PACKING GROUP: Not Applicable.

DOT LABEL(S) REQUIRED: Not Applicable

NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER (2004): Not Applicable

MARINE POLLUTANT: None of the ingredients are classified by the DOT as a Marine Pollutant (as defined by 49 CFR 172.101, Appendix B)

U.S. DEPARTMENT OF TRANSPORTATION (DOT) SHIPPING REGULATIONS:

This product is not classified as dangerous goods, per U.S. DOT regulations, under 49 CFR 172.101.

TRANSPORT CANADA, TRANSPORTATION OF DANGEROUS GOODS REGULATIONS:

This product is not classified as Dangerous Goods, per regulations of Transport Canada.

INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA):

This product is not classified as Dangerous Goods, by rules of IATA:

INTERNATIONAL MARITIME ORGANIZATION (IMO) DESIGNATION:

This product is not classified as Dangerous Goods by the International Maritime Organization.

===== Section 15 - Regulatory Information =====

UNITED STATES REGULATIONS

SARA REPORTING REQUIREMENTS:

This product is not subject to the reporting requirements Of Sections 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act., as follows: None

TSCA:

All components in this product are listed on the US Toxic Substances Control Act (TSCA) inventory of chemicals.

SARA 311/312:

Acute Health: Yes Chronic Health: No Fire: No Reactivity: No

U.S. SARA THRESHOLD PLANNING QUANTITY:

There are no specific Threshold Planning Quantities for this product. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lb (4,540 kg) may apply, per 40 CFR 370.20.

U.S. CERCLA REPORTABLE QUANTITY (RQ):

None

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65):

One or more of the ingredients are on the California Proposition 65 lists.

WARNING! This product contains ingredients that are known to the State of California to cause cancer or reproductive harm.

CANADIAN REGULATIONS:

CANADIAN DSL/NDSL INVENTORY STATUS:

SEAL TECH PRO X SAFETY DATA SHEET

All of the components of this product are on the DSL Inventory

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS:

No component of this product is on the CEPA First Priorities Substance Lists.

CANADIAN WHMIS CLASSIFICATION and SYMBOLS:

This is not considered to be a hazardous material under the Hazardous Products Act as defined by the Controlled Products Regulations and is therefore not subject

===== Section 16 - Other Information =====

DISCLAIMER

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied regarding its correctness or suitability for consumers intended use and /or application. For this and other reasons, SEAL TECH assumes no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If there are any problems or concerns understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at 1(800) 535-5053.

SEAL TECH components are provided as basis without warranties of any kind either expressed or implied. SEAL TECH does not warrant the use or the results of use of the materials sold on an as is basis since they are intended for remanufacturing or repackaging. It is the sole responsibility of the user to examine and determine appropriate application and regulatory requirements associated with said SEAL TECH components.